

IN THE U.S. PATENT AND TRADEMARK OFFICE

In re application of

Georg STROBL

Conf.

Application No. NEW NON-PROVISIONAL

Group

Filed March 11, 2004

Examiner

ELECTRIC MOTOR

CLAIM TO PRIORITY

Assistant Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

March 11, 2004

Sir:

Applicant(s) herewith claim(s) the benefit of the priority filing date of the following application(s) for the above-entitled U.S. application under the provisions of 35 U.S.C. § 119 and 37 C.F.R. § 1.55:

<u>Country</u>	<u>Application No.</u>	<u>Filed</u>
GREAT BRITAIN	0306077.9	March 18, 2003

Certified copy(ies) of the above-noted application(s) is(are) attached hereto.

Respectfully submitted,

YOUNG & THOMPSON



Benoit Castel, Reg. No. 35,041
745 South 23rd Street
Arlington, VA 22202
Telephone (703) 521-2297
Telefax (703) 685-0573
703) 979-4709

BC/yr

Attachment(s): 1 Certified Copy(ies)



INVESTOR IN PEOPLE


The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 24 February 2004

18 MAR 2003

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

MRH.PO4788GB / P371

2. Patent application number

(The Patent Office will fill in this part)

0306077.9

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Johnson Electric S.A.
Rue Fritz-Courvoisier 40
CH-2300 La Chaux-de-Fonds
Switzerland

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

4018312005
Switzerland

4. Title of the invention

ELECTRIC MOTOR

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Marks & Clerk
27 Imperial Square
Cheltenham
GL50 1RQ

Patents ADP number (if you know it)

18014

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

Yes

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description	5
Claim(s)	3
Abstract	1
Drawing(s)	2 + 2

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*) 1

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature  Date 17th March 2003
Marks & Clerk

12. Name and daytime telephone number of person to contact in the United Kingdom Mr M R Higgins
01242 524520

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Electric Motor

This invention relates to an oscillating electric motor and in particular, to a miniature oscillating motor suitable for use in portable battery powered appliances.

5

Oscillating motors are devices which look like a motor in that they have an output shaft extending from a housing. However, the output shaft does not fully rotate but instead oscillates back and forth through a limited range of movement of less than one revolution, often though only a few degrees, for example, 30° or 60°.

10

US 4595849 shows such a motor for use in an electric toothbrush. The motor has a permanent magnet rotor and a return spring for biasing the rotor to a rest position. A flywheel is fitted to the motor shaft to fine tune the resonance frequency of the rotor so that resonance occurs at operating frequency.

15

There is a need for an oscillating motor which is simple in construction, reliable and is easy to mass produce.

Accordingly, the present invention provides a motor as defined in claim 1.

20

Preferred features of the invention, as shown in the preferred embodiments described, are set forth in the dependent claims.

25

Preferred embodiments of the invention will now be described with reference to the accompanying drawings, in which:

Figure 1 is a cross-sectional view of a motor according to the preferred embodiment;

Figure 2 is a longitudinal sectional view of the motor of Figure 1;

30

Figure 3 is a longitudinal sectional view similar to Figure 2 of a modified motor;

Figure 4 is cross sectional view of an end cap of the motor of Figure 3;

35

Figure 5 is a longitudinal sectional view similar to Figure 2 of a further modified motor; and

Figure 6 is a elevational view of a seal bearing as used in the motor of Figure 5.

The oscillating motor of the preferred embodiment has a simple construction with an angular movement of $\pm 15^\circ$ from a spring biased neutral or rest position. Figure 1 is a cross section through the middle of the motor showing the construction of the stator and rotor.

The rotor 11 comprises a laminated rotor core 21 with two salient poles 12 fitted to a motor shaft 20. There are no windings or magnets associated with the rotor 11. The stator has a ring type laminated stator core 15 having two salient stator poles 16. A stator coil 17 is wound around each stator pole 16. The stator also has two permanent magnets 13 circumferentially spaced between the stator poles 16 and located in confrontation with the rotor poles 12. The magnets 13 are magnetised laterally so as to have a N-pole and a S-pole next to each other as shown in Figure 1 with the magnets arranged to provide a north pole and a south pole adjacent each stator pole 16.

The stator poles 16 face a body portion of the rotor core 21 across a small air gap 18 and the rotor poles 12 face the permanent magnets 13 across a small air gap 14 with the rotor being naturally biased by the magnets 13 to a neutral or rest position midway between the poles of the magnets which coincides with the middle of the magnets 13. The rotor 11 is also spring biased to the rest position. The function of this spring bias will be described in detail hereinafter.

As shown in Fig. 2, a plastic housing 22 covers the stator core 15. An end cap 23 closes off an open end of the housing. The shaft 20 is supported in bearings 24, 25 fitted to the housing 22 and the end cap 23. The end cap 23 also supports a torsion spring 19. The torsion spring 19 is a flat strip of spring steel secured in a slot in the end of the shaft 20. The spring 19 extends axially from the end of the shaft 20 and is located in a corresponding slot 26 of the end cap 23.

Operation of the motor will now be described. In the inactive state, the permanent magnets 13, assisted by the spring 19 returns or maintains the rotor 11 in its rest position in which the rotor poles 12 are equally attracted to both poles of the permanent magnets 13. When the motor is turned on current is passed through the stator coils 17 causing a magnetic field to be induced in the stator poles 16. Current in one direction produces a north magnetic pole to be formed on both stator poles 16. This in turn induces a north pole on both rotor poles 12 causing the rotor to swing toward the south poles of the magnets 13 as the forces of attraction between the south

poles of the magnets and the north poles of the rotor and the forces of repulsion between the rotor north poles and the magnet north poles are greater than the restraining force of the spring 19 so that the rotor poles 12 are now aligned with the south poles of the magnets 13.

5

When current is fed through the stator coils in the opposite direction, a south magnetic pole is created in both stator poles 16 causing the rotor to swing in the opposite direction to align with the north poles of the magnets 13.

10 When no current is flowing through the coils 17, the stator poles 16 are no longer magnetised and there is no magnetic field induced in the rotor poles 12 and the rotor 11 returns to its rest position under the influence of the spring 19 and the permanent magnets 13.

15 By feeding alternating current through the stator coils 17, the rotor 11 swings from north poles to south poles and back, producing an continuous oscillating motion of the output shaft 20. It is envisaged that the a.c. supply would be provided by a battery driven electronic oscillator circuit.

20 The angle of oscillation can be predetermined with a maximum allowed movement set by physical constraints in the construction of the motor but the output range is of course dependent on the circumferential or arcuate extent of the permanent magnets 13, the strength or stiffness of the spring 19, the strength of the magnetic fields and the natural resonance frequency of the system and the operating frequency.

25

One preferred no load operating condition is a swing of $\pm 15^\circ$ at a resonance frequency between 150 - 350 Hz.

The motor operates most effectively when the operating frequency matches the
30 resonance frequency of the rotating system. The resonance frequency is affected primarily by the mass of the rotor and any attachments thereon, the rotating mass. However, for certain applications such as toothbrushes and shavers, the desired output frequency may be above the resonance frequency of the rotating mass. The spring bias is used to adjust upwardly the resonance frequency of the rotating mass. It is
35 thought that this occurs by increasing the acceleration of the rotor towards the rest position as the current is reversed in the stator coils. The faster the acceleration, the higher the resonance frequency. Thus by increasing the spring bias, e.g., by using a stiff spring, the resonance frequency of the motor is increased. By selecting an

appropriate spring, the resonance frequency of the motor can be matched to the operating frequency to provide the greatest efficiency and thus the longest operating time per battery charge.

- 5 The bearings 24, 25 for the rotor must operate on only a small rotation in each direction and thus, oil impregnated sintered bearings, the bearing of choice for miniature electric motors, may not be suitable. Preferred bearings are the hard plastic bushings coated with self lubricating, or low friction material such as PTFE or NiPTFE, nylon bushings and/or ceramic bushings.

10

- Figure 3 shows a motor similar to that of Figure 2 in which the bearings 24, 25 are ball bearings and the return spring 19 is in the form of a leaf spring placed radially instead of axially. The operating principle is the same. Figure 4 is a cross sectional view of the inside of the end cap 23 of the motor of Figure 3 to illustrate the arrangement of the return spring 19. The spring 19 is a flat strip of spring steel located in a slot in the end of the shaft 20. The spring 19 extends radially from the shaft 20 and both ends of the spring are located in respective recesses 26 in the end cap 23 in a manner to allow slight radial sliding of the spring while preventing the spring 19 from rotating with the shaft 20. Thus as the shaft 20 rotates the spring 19 is coiled or otherwise resiliently deformed creating a restoring force acting on the shaft 20 to return the rotor 11 to the rest position.

- Figure 5 illustrates a further modified motor similar to the motor of Figure 2 in which the spring and bearing are combined into a single special bearing unit which also seals the end of the motor housing which is important for wet applications such as for use in an electric toothbrush or an electric shaver.

- This special bearing unit referred to hereinafter as rubber bearing 24 is shown in Figure 6. The rubber bearing 24 has an outer ring 27 for press fitting to the motor housing 22 or end cap 23 and an inner ring 28 for fitting onto the shaft 20. A number of ribs 29 extend between the inner and outer rings 28, 27 and provide radial support for the shaft 20. A web or rubber sheet 30 extends between each rib 29 and the inner and outer rings 28, 27 to seal the opening. The inner ring 28 is vulcanized to the shaft 20 to provide a good watertight seal and fixation. To give better grip or adhesion between the shaft 20 and the inner ring 28, the shaft 20 may be provided with a feature 31, such as flats, cuts or knurls. The inner ring may be similarly shaped. Thus, the inner ring 28 rotates with the shaft 20 and such rotation causes elastic

distortion of the ribs 29 which provides the spring force required to modify the resonance frequency of the rotor and to bias the shaft 20 to the rest position.

5 This bearing arrangement is particularly attractive when the angle of oscillation is small, say in the order of ± 5 to 10° . The material of the special bearing unit is preferably rubber or rubber like material especially silicone rubber with or without a metal or plastic insert.

10 The embodiments described above are given by way of example only and various modifications will be apparent to persons skilled in the art without departing from the spirit and scope of the invention as defined in the appended claims. For example, each permanent magnet may be made up of a number of separate permanent magnet pieces.

Claims

1. An oscillating motor comprising
a shaft;
5 a laminated rotor core fitted to the shaft, the rotor core having at least one salient pole;
a laminated stator core having at least one salient pole;
at least one stator coil wound about the stator pole;
at least one permanent magnet fitted to the stator core located
10 circumferentially spaced from the stator pole and facing the rotor pole across an air gap, the permanent magnet having two circumferentially spaced magnetic poles;
whereby alternating current flowing through the stator coil causes the rotor pole to swing between the poles of the permanent magnet.
- 15 2. An oscillating motor according to claim 1 wherein
the rotor core has two salient poles;
the stator core has two salient poles, each stator pole having a respective stator coil;
there are two permanent magnets fitted to the stator core respectively located
20 circumferentially between the stator poles and respectively facing the rotor poles across an air gap;
wherein the stator coils are wound to induce like magnetic poles in the stator poles which in turn induce like magnetic poles in the rotor poles.
- 25 3. An oscillating motor according to claim 1 or 2 wherein the rotor is biased to a rest position by a return spring.
4. A motor according to claim 3 wherein the return spring is a torsion spring in the form of a strip of spring steel attached at one end to the shaft and at another end to
30 a stationary part of the motor.
5. A motor according to claim 4 wherein the spring has a first end fixed in a slot in an end of the shaft and has a second end located in a slot in the end cap, with the spring extending in the axial direction of the shaft.
- 35 6. A motor according to claim 4 wherein the spring is located in a slot in the shaft, extends radially of the shaft and the ends of the spring are located in recesses in the end cap.

7. A motor according any one of the preceding claims wherein the permanent magnets are composed of a number of separate smaller permanent magnet pieces.

5 8. A motor according to any one of the preceding claims wherein the motor has a cup shaped housing closed at one end by an end cap, the housing and end cap each supporting a bearing for rotationally supporting the shaft.

9. A motor according to claim 8 wherein the bearings are bushings with a shaft
10 interface surface of self lubricating or low friction material.

10. A motor according to claim 9 wherein the low friction material is NiPTFE, PTFE, nylon or hard plastics.

15 11. A motor according to claim 8 wherein one of the bearings is a special bearing which provides a spring function to urge the shaft into a predetermined orientation.

12. A motor according to claim 11 wherein the special bearing also seals the shaft to the housing to prevent ingress of moisture.

20

13. A motor according to claim 12 wherein the special bearing and the end cap seal the shaft to the housing.

14. A motor according to claim 13 wherein the special bearing comprises an outer
25 ring fixed to the housing or end cap, an inner ring fixed to the shaft for rotation therewith, a web extending between the inner and outer rings and a plurality of ribs extending between the inner and outer rings.

15. A motor according to claim 14 wherein the special bearing is a single casting
30 of a resiliently deformable material.

16. A motor according to claim 15 wherein the material of the special bearing is selected from the group consisting of rubber, synthetic rubber, rubber like materials and silicone.

35

17. A motor according to claim 14 wherein the special bearing is vulcanized to the motor shaft.

18. A motor according to any one of the preceding claims wherein the shaft oscillates in an angular range between $\pm 5^\circ$ and $\pm 20^\circ$, preferably between $\pm 5^\circ$ and $\pm 10^\circ$.

19. A motor according to any one of the preceding claims wherein the motor is
5 arranged to operate on an a.c. supply frequency of between 150 Hz to 350 Hz (output of 150 to 350 oscillations per second).

20. An oscillating motor substantially as hereinbefore described with reference to the accompanying drawings.

Abstract

An oscillating motor 10 has a rotor rotation of about $\pm 15^\circ$ from a rest position. The rotor 11 has two salient poles 12 which face a respective permanent magnet 13 across a small air gap 14. The stator has a laminated stator core 15 supporting the magnets 13 and also two salient poles 16 each supporting a stator coil 17. The stator poles 16 confront the rotor across a small air gap 18 between the rotor poles. When no current is flowing through the coils, the rotor 11 rests in a rest position with the poles 12 aligned between the north and south poles of the magnets 13. During operation, the stator coils 17 induce like magnetic poles in the stator poles 16 which in turn induce like magnetic poles in the rotor poles 12 causing the rotor 11 to swing towards opposite magnetic poles of the permanent magnets 13. When current flows in the reverse direction, the rotor 11 swings to the opposite poles of the magnets 13. Passing alternating current through the stator coils 17 causes the rotor 11 to swing or oscillate continuously through a small angular range.

Figure 1

1/2




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 6




FIG. 5